

Product Information

Dry Flow Firm

Physical Properties*

DENSITY	30.0 -34.0 kg/m ³	I.F.D. HARDNESS RANGE (NEWTONS)
TEAR RESISTANCE	400N/m Minimum	IF 40% Minimum 250N
TENSILE STRENGTH	85kPa Minimum	IF 40% Maximum 290N
ELONGATION	180% Minimum	
RESILIENCE	40% Minimum	
COMPRESSION SET (75%)	6% Maximum	

* When tested internally in accordance with the test methods listed in Australian Standard AS2282.0

Available Colour

Off White

Grade Description

Reticulated foams with approximately 20-40 cells/25mm

Typical Applications

Ideal for use in commercial grade furniture - seat and back cushion / mattress / bedding applications

For effective use and warranty guarantee, outdoor acrylic fabrics must be used on all sides of the cushions/mattresses so that the foam is able to dry effectively (e.g. Sunbrella material is suitable). Foam can be cut to various sizes. However, minimum thickness of 25mm is a warranty condition.

For best results, rinse with cold water (no chemicals to be used in cleaning process), allow to dry in shade, air regularly.

Information current as at May 2017

Contact Dunlop Foams

447 Foleys Rd, Deer Park, VIC 3023

Phone: 1800 736 634 or +617 3345 3644 Fax: 1800 736 994

Email: enquires@dunlopfoams.com.au