

## Product Information

# Dry Flow Soft

### Physical Properties\*

|                              |                               |  |
|------------------------------|-------------------------------|--|
| <b>DENSITY</b>               | 23.0 - 27.0 kg/m <sup>3</sup> | <b>I.F.D. HARDNESS RANGE (NEWTONS)</b> |
| <b>TEAR RESISTANCE</b>       | 400N/m Minimum                | IF 40% Minimum 140N                    |
| <b>TENSILE STRENGTH</b>      | 85kPa Minimum                 | IF 40% Maximum 180N                    |
| <b>ELONGATION</b>            | 180% Minimum                  |  |
| <b>RESILIENCE</b>            | 40% Minimum                   |  |
| <b>COMPRESSION SET (75%)</b> | 6% Maximum                    |  |

\* When tested internally in accordance with the test methods listed in Australian Standard AS2282.0

### Available Colour

Off White

### Grade Description

Reticulated foams with approximately 20-40 cells/25mm

### Typical Applications

Ideal for use in commercial grade furniture - seat and back cushion / mattress / bedding applications

*For effective use and warranty guarantee, outdoor open weave fabrics must be used on all sides of the cushions/mattresses so that the foam is able to dry effectively. Foam can be cut to various sizes. However, minimum thickness of 100mm is a warranty condition.*

*For best results, rinse with cold water (no chemicals to be used in cleaning process), allow to dry in shade, air regularly.*

Information current as at May 2017

#### Contact Dunlop Foams

447 Foleys Rd, Deer Park, VIC 3023

Phone: 1800 736 634 or +617 3345 3644 Fax: 1800 736 994

Email: [enquires@dunlopfoams.com.au](mailto:enquires@dunlopfoams.com.au)