



DESCRIPTION

Old world traditional antiqued leather with classic sophistication. A natural addition to any club house, formal or executive environment.

SPECIFICATIONS

Average Hide Size		55 sqft / 5.11 sqmt
Thickness		1.0 - 1.2 mm
PERFORMANCE CHA	ARACTERISTICS	
Light Fastness	(AATCC Method 16, Option E)	3
Tear Strength	(ASTM D4705)	28 lbs.
Flexing Endurance	(ASTM D2097)	Pass
Abrasion	(ASTM D3884)	500 Cycles
Elongation	(ASTM D2211)	30 - 45% at 50 lbs.
Crocking	(ASTM D5053)	Wet:3 Dry: 4
Breaking Force	(ASTM D2208)	180 lbs.
FLAMMABILITY		
Boston Fire Dept. Code (BFD 1x-1) w/Fire Blocker and or Fire Barrier Cloth		Pass
California Technical Bulletin 117		Pass
Cigarette Ignition Resistance	(NFPA 260)	Class 1
California Technical Bulletin 133 w/Fire Blocker and/or Fire Barrier Cloth		Pass

CLEANING INSTRUCTIONS

Natural, aniline leathers have little surface protection. If your aniline leather does become soiled, immediately blot excess liquid with a soft, clean cloth. Then clean the entire area (i.e. the entire seat cushion, arm rest, etc.) with a clean, damp cloth and clear luke warm water, starting from the outside of the spill to the center.

Do not use: Any saddle soaps, oils, abrasives, cleaners, soaps, furniture polish, varnish or ammonia water.

Please note: Due to the natural characteristics of this leather, scratches and marks may appear over time. This appearance is the "character" of the natural leather.