

SOLARTEX

Specification Sheet

The Solartex range are premium marine and outdoor fabrics manufactured from 100% acrylic, outdoor graded fibre. Suitable for use in boating hooding, bimini covers and boat covers, Solartex is also ideal for awning, window and blind applications. Specially coated with TECNOGARD finish, Solartex is stain and mildew resistant, colour fast and breathable.

Characteristics

- Resistant to mould and bacteria
- Stain repellent
- Breathable
- Colour fast
- Reduces maintenance and cleaning costs
- Longer service life of boat
- Oeko-Tex® Standard 100 certified
- TECNOGARD coated and sanitised
- Five year guarantee





SPECIFICATIONS		SOLARTEX	SOLARTEX PU BACKED
COMPOSITION			
TOTAL WEIGHT (GSM)	UNI 5114/82	300	320
WIDTH (CM)	UNI EN 1773/98	200	200
COLOURS		9	8
ROLL LENGTH (LM)		50	50
WEAVE	UNI 8099/80	WARP 30 ENDS/CM WEFT 14 ENDS/CM	WARP 30 ENDS/CM WEFT 14 ENDS/CM
BREAKING LOAD	UNI EN ISO 13934- 1/00	WARP > 1400N WEFT > 800N	WARP > 1275N WEFT > 784N
COLOUR FASTNESS	EN ISO105-B04/00	7/8	7/8
WATER REPELLENCY	UNI EN105-B04-00	WATER REPELLENT	WATER REPELLENT
IMPERMEABILITY	UNI EN 20811/93		60CM FOR 24 HOURS
WATER COLUMN	UNI EN 20811/93	NOT LOWER THAN 30CM	
FINISH		TECNOGARD TREATED	TECNOGARD TREATED, WATERPROOF
CARE		GENTLE WASH (30°C) WITH NEUTRAL SOAP. RINSE THOROUGHLY. DO NOT USE DETERGENT	
GUARANTEE		5 YEARS	5 YEARS